



## OBY 500B



Glasswasher



- **Stainless Steel Body** including washing and boiler tank
- **Hygienic washing tank**
- **30 racks per hour** (Rack dimension 35 x 35)
- **2.5 l water consumption per cycle**
- **Automatic, user friendly control panel**
- **1 Washing Programme - Cycle 120 seconds**
- **Saves energy, detergent and water**
- **Washing arms in reinforced polypropylene**
- **Adjustable feet for height optimization**
- **Easy start up: Single button for water filling and heating in the boiler tank**
- **Electrical components and cabling according to international standards and safety regulations.**
- **Completely sealed body to guarantee IPX5 water protection**
- **Thermostat-controlled rinsing and washing temperatures for efficient washing**
- **Non-return - Check valve System**
- **Washing temperature at 55-60°C** (water supply at a minimum of 2 bar and 50°C)
- **Rinsing temperature at 80-85°C** (water supply at a minimum of 2 bar and 50°C)

### STANDART EQUIPMENT

Rinse Aid Dispenser  
1 Glass Rack Promotional with cutlery and cup holders  
Electrical Connection Cable, Flexible Water Supply and Drain Hose

### OPTIONAL EQUIPMENT

Detergent Dispenser  
Drain Pump

| Technical Features               | OBY 500 B          |
|----------------------------------|--------------------|
| Code                             | 0710.00500.02      |
| Total power                      | 3.3 kW             |
| Electric connection              | 230V~NPE / 50Hz    |
| Washing capacity (Glass/hr)      | 500 glass / bardak |
| Washing capacity (Basket/hr)     | 30                 |
| Washing / Boiler tank capacity   | 9.2 / 2.8 lt.      |
| Washing water temp.              | 55-60°C            |
| Rinsing water temp.              | 80-85 °C (max.)    |
| Washing program number           | 1                  |
| Water inlet connection           | 3/4 "              |
| Washing pump power               | 0.27 kW            |
| Rinsing pump power               | -                  |
| Water inlet pressure / Temp.     | 2-4 Bar / 50 °C    |
| Heat power (Washing/Rinsing)     | 2 / 3 kW           |
| Dirty water discharge connection | 3/4" (28 mm)       |
| Max. noise                       | 85 dBA             |
| Gross weight                     | 35 (±5) kg         |
| Dimensions (LxWxD)               | 420x450x620 mm     |
| Protection class                 | IPX5               |
| Rack dimensions                  | 35 x 35 cm         |
| Loading height                   | 20 cm              |
| Price                            |                    |



OBY 500  
OBY 500E  
OBY 500 PLUS





 TÜV-CB  
Dishwasher

- Stainless Steel Body including washing and boiler tank
- Hygienic washing tank
- 35 racks per hour (Rack dimension 50 x 50)
- 2.8 l water consumption per cycle
- Automatic, user friendly control panel
- 2 Washing Programme - - Cycle 102-192 seconds
- Saves energy, detergent and water
- Washing arms both available in stainless steel and reinforced polypropylene
- Adjustable feet for height optimization
- Easy start up: Single button for water filling and heating in the boiler tank
- Electrical components and cabling according to international standards and safety regulations.
- Completely sealed body to guarantee IPX5 water protection
- Thermostat-controlled rinsing and washing temperatures for efficient washing
- Non-return - Check valve System
- Washing temperature at 55-60°C (water supply at a minimum of 2 bar and 50°C)
- Rinsing temperature at 80-85°C (water supply at a minimum of 2 bar and 50°C)

| STANDART EQUIPMENT                                                | OBY 500 | OBY 500 E | OBY 500 PLUS |
|-------------------------------------------------------------------|---------|-----------|--------------|
| Detergent Dispenser                                               | OPT     | OPT       | ✓            |
| Rinse Aid Dispenser                                               | ✓       | ✓         | ✓            |
| Rinsing Pump                                                      | ✓       | N / A     | ✓            |
| Drain Pump                                                        | OPT     | OPT       | ✓            |
| 3 Baskets Promotional (Plate, Glass and Cutlery )                 | ✓       | ✓         | ✓            |
| Electrical Connection Cable, Flexible Water Supply and Drain Hose | ✓       | ✓         | ✓            |
| Stainless Steel Washing Arms                                      | OPT     | OPT       | OPT          |

| Technical Features               | OBY 500         | OBY 500 E       | OBY 500 PLUS    |
|----------------------------------|-----------------|-----------------|-----------------|
| Code                             | 0710.00500.01   | 0710.00500.00   | 0710.00500.03   |
| Total power                      | 5.5 kW          | 5.5 kW          | 5.5 kW          |
| Electric connection              | 230V~NPE / 50Hz | 230V~NPE / 50Hz | 230V~NPE / 50Hz |
| Washing capacity (Plate/hr)      | 560 (max.)      | 560 (max.)      | 560 (max.)      |
| Washing capacity (Basket/hr)     | 35              | 35              | 35              |
| Washing / Boiler tank capacity   | 30 / 6lt.       | 30 / 6lt.       | 30 / 6lt.       |
| Washing water temp.              | 55-60 °C        | 55-60 °C        | 55-60 °C        |
| Rinsing water temp.              | 80-85 °C (max.) | 80-85 °C (max.) | 80-85 °C (max.) |
| Washing program number           | 2               | 2               | 2               |
| Water inlet connection           | 3/4 "           | 3/4 "           | 3/4 "           |
| Washing pump power               | 0.66 kW         | 0.66 kW         | 0.66 kW         |
| Rinsing pump power               | 0.37 kW         | -               | 0.37 kW         |
| Water inlet pressure / Temp.     | 2-4 Bar / 50°C  | 2-4 Bar / 50 °C | 2-4 Bar / 50°C  |
| Heat power (Washing/Rinsing)     | 2 / 5 kW        | 2 / 5 kW        | 2 / 5 kW        |
| Dirty water discharge connection | 1 1/4" (42 mm)  | 1 1/4" (42 mm)  | 1 1/4" (42 mm)  |
| Max. noise                       | 85 dBA          | 85 dBA          | 85 dBA          |
| Gross weight                     | 75 (±5) kg      | 70 (±5) kg      | 75 (±5) kg      |
| Dimensions (LxWxD)               | 600x670x820 mm  | 600x670x820 mm  | 600x670x820 mm  |
| Protection class                 | IPX5            | IPX5            | IPX5            |
| Rack dimensions                  | 50 x 50 cm      | 50 x 50 cm      | 50 x 50 cm      |
| Loading height                   | 30 cm           | 30 cm           | 30 cm           |
| Price                            |                 |                 |                 |



**OBY 500D**

Dishwasher



- Stainless Steel Body including washing and boiler tank
- Hygienic washing tank
- 35 racks per hour (Rack dimension 50 x 50)
- 2.8 l water consumption per cycle
- Automatic, user friendly control panel
- Temperature Indication on front panel
- 5 Selectable Washing Programmes
- Saves energy, detergent and water
- Washing arms both available in stainless steel and reinforced polypropylene
- Adjustable feet for height optimization
- Easy to use electronic control panel
- Easy start up: Single button for water filling and heating in the boiler tank
- Electrical components and cabling according to international standards and safety regulations.
- Completely sealed body to guarantee IPX5 water protection
- Thermostat-controlled rinsing and washing temperatures for efficient washing
- Non-return - Check valve System
- Washing temperature at 55-60°C (water supply at a minimum of 2 bar and 50°C)
- Rinsing temperature at 80-85°C (water supply at a minimum of 2 bar and 50°C)

## STANDART EQUIPMENT

Rinse Aid Dispenser  
 Rinsing Pump  
 3 Baskets Promotional (Plate, Glass and Cutlery )  
 Electrical Connection Cable, Flexible Water Supply and Drain Hose

## OPTIONAL EQUIPMENT

Stainless Steel Washing Arms  
 Detergent Dispenser  
 Drain Pump

| Technical Features               | OBY 500 D          |
|----------------------------------|--------------------|
| Code                             | 0710.00500.05      |
| Total power                      | 230V - NPE / 50 Hz |
| Electricity connection           | 5.5 kW             |
| Washing capacity (Plate/hr)      | 560 (max.)         |
| Washing capacity (basket / hr)   | 35                 |
| Washing / Boiler tank capacity   | 30 / 6 lt.         |
| Washing water temp.              | 55 - 60 °C         |
| Rinsing water temp.              | 80 - 85 °C (max.)  |
| Washing program number           | 5                  |
| Water inlet connection           | 3/4 "              |
| Washing pump power               | 0,66 kW            |
| Rinsing pump power               | 0,37 kW            |
| Water inlet pressure / Temp.     | 2 - 4 Bar / 50 °C  |
| Heat power (Washing/Rinsing)     | 2/ 5 kW            |
| Dirty water discharge connection | 1 1/4 " (Ø 42 mm)  |
| Max. noise                       | 85 dBA             |
| Gross weight                     | 75 (±5) kg         |
| Dimensions (LxWxD)               | 600x670x820 mm     |
| Protection class                 | IP X5              |
| Rack dimensions                  | 50 x 50 cm         |
| Loading height                   | 30 cm              |
| Price                            |                    |